

NKB1000-E

Network Keyboard



Features :

Keyboard to Control

- High Speed Dome
- Standalone DVR
- Network Video Server

Connection

- RS485, RS422 (reserved), USB, RS232 & Network

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS or DSS platform via USB



Technical Specification

Model

Model NKB1000-E

General

Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422 (reserved), USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: 1 RS232/2 RS485 DVR Protocol: DH-2 Dome Protocol: DH-SD1/PELCO-D/PELCO-P, etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Display	LCD, 75.2mm×33.85mm
Maximum Number of Users	64 (including "admin")
Max RS485 Addresses (Each User)	256
Max Number of PTZ (IPC) That Can be Added over Network (Each User)	2048

Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/2A
Power Consumption	5W
Working Temperature	-10 C~+55 C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×139mm×53mm (W×D×H)(height: 103mm including joystick)
Weight	1.3kg (Including package)

Dimensions(mm)

